

# Ultimate Seats

## VTX ARMREST INSTALLATION

**Installs on Honda Standard backrest sissy bar. (with standard clamp)**

1. Before you start, place a thick cloth over the fender below the area
2. Remove the nuts holding the passenger pad on the Sissy Bar and remove the pad.
3. Remove the 2 outside nuts and bolts from the clamp bracket.
4. Take the entire armrest and standing behind the Sissy Bar tilt the armrest so the clamp bracket can fit through the Sissy Bar.
5. Place the bracket just above or just below the 2 bolt pads, use these 2 pads to rest the mounting bolts against, this will also level the armrest.
6. Reinstall the 2 outside nuts and bolts in the clamp bracket.
7. Have your passenger sit on the bike and make the height adjustment up or down and tighten the clamp.
8. Reinstall the passenger pad.
- 9. When dismounting you must first flip up the armrest .... Do not use them to push yourself up .... They are not intended to be used in this manner. Please make sure your passenger is told this. Damage to the hinge will occur if they are used incorrectly.**

Your new armrest has a quick release hinge pin so if you wish to remove the armrest and leave the mounting bracket attached to the backrest just slide out the hinge pin and remove the arms.

Questions ? call us on 1-800-818 6868 or email [des@ultimateseats.ca](mailto:des@ultimateseats.ca)  
Web site [www.ultimateseats.ca](http://www.ultimateseats.ca)