

**Electra Glide/Ultra/Road Glide
Road King/Street Glide
2009 and up
ONE PC SEAT
Ultimate seats Installation**

Install kit for Road King and Street Glide

3 stainless spacers

3 screws 1/4" – 20 x 1.5" long (for optional sissybar pad)

Removal of Stock Seat

1. If you have a seat strap remove saddlebags.
2. Remove the two saddlebag mount brackets (one each side) holding the seat strap.
3. Remove the strap and store it then replace the two saddlebag mounts in their original position.
4. Remove the rear fender bolt from seat.
5. Slide seat back and up to remove.

Install your new seats.

Important, remove the two torque bolts and spacer blocks on top of the frame on each side and store away.

1. Install your Ultimate seat now, make sure you have the front locating bracket on the seat nose located properly in the bike frame under the tank and install the stock screw in the rear bracket on the seat and fasten correctly.
2. Reinstall your saddlebags.

Remove/Install sissybar pad (optional)

Remove the 3 screws holding the stock pad and remove, store the pad and the plastic spacers.

Install the Ultimate pad using the 3 supplied stainless spacers and install with the stock screws, if they are not long enough use the new supplied screws.

Enjoy the ride again on your Ultimate seats

Questions ??? call us on 1-877-672 0288

or email des@ultimateseats.ca

Web site – www.ultimateseats.ca